

VERSO® PRODUCT DATA SHEET

PRODUCT CODE

VCP110CR-T

PRODUCT RANGE

Circuit Protection Devices

DESCRIPTION

10A 30mA Type A 6kA Single Pole
RCBO C Curve

FEATURES

- Individually tested
- No Earth fly lead
- Combines RCD protection with MCB functionality. Allowing earth fault protection to be restricted to a single circuit.
- Available from 6A to 50A in B & C curve



TECHNICAL INFORMATION

| | |
|----------------------------------|--|
| Height | 112mm |
| Width | 17mm |
| Depth | 67mm |
| Weight | 0.168 Kg |
| Short Circuit rating | 6kA |
| Terminal capacity (out) | 10mm ² |
| Torque settings (out) | 1.2Nm |
| Torque settings (In) | 2.0Nm |
| Ambient temperature | -5 to +55 C |
| Integral MCB Type | C Curve |
| Number of Poles | Single Pole (Switched Live with Solid Neutral) |
| Mounting type | Din Rail |
| Guarantee | 10 Years |
| Frequency | 50/60Hz |
| Current Rating | 10A |
| Cable Clamp type | Sqaure cage clamp mechanism |
| Rated operating voltage | 230/240 AC |
| Number of modules | One |
| IP Rating | IP2X |
| Packaging type | Singular |
| Operating characteristic | Type A |
| Rated residual operating current | 30mA |
| Lockable | Yes |
| Standards | BS EN 61009-1 |
| Certified Independantly by | TUV Rheinland - Germany |
| Country of origin | PRC |

VERSO® DECLARATION OF CONFORMITY

PRODUCT CODE

VCP110CR-T

DESCRIPTION

10A 30mA Type A 6kA Single Pole
RCBO C Curve

INTENDED USE

To protect against overcurrent and short
circuit and earth leakage.

MANUFACTURER

Verso® Electrical
PGL House (Floor 1), West Point Industrial
Estate. Penarth Road. Cardiff. CF11 8JQ.
United Kingdom

RATINGS & CHARACTERISTICS

| | |
|----------------|----------|
| Voltage Rating | 230V AC |
| Current Rating | 10A |
| Frequency | 50/60 Hz |

DESIGNATED STANDARDS

BS EN 61009
BS EN 61009-2-1
BS EN 61543 (1995-96)



I declare that the object of the declaration above is in conformity with the relevant harmonization legislation
and national standards.

Signed on behalf of Verso® Electrical

William Winter (Ba/Bsc) | Managing Director